

SPMBPI - BPI inks series

Revision nr. 1

Dated 11/7/2013

Printed on 11/07/2013

Page n. 1/10

# Safety data sheet

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: SPMBPI
Product name BPI inks series

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Permanent marker inks

1.3. Details of the supplier of the safety data sheet

Name PLUSS S.R.L.
Full address Via M. Ponzio, 42/A
District and Country 27100 Pavia (PV)

Italia

tel. +39 0382 472106 fax +39 0382 565917

e-mail address of the competent person

responsible for the Safety Data Sheet stefano@pluss.it

1.4. Emergency telephone number

For urgent inquiries refer to +39 0382 472106

## SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

R phrases:

10-67

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

## 2.2. Label elements.

Hazard labelling pursuant to Directives 67/548/EEC and 1999/45/EC and subsequent amendments and supplements.

Warning symbols: None.

R10 FLAMMABLE.

R67 VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

S43 IN CASE OF FIRE, USE CO2, FOAM, DRY CHEMICAL POWDER. 'NEVER USE WATER'.

#### 2.3. Other hazards.



Revision nr. 1

Dated 11/7/2013

Printed on 11/07/2013

Page n. 2/10

# SPMBPI - BPI inks series

Information not available.

# **SECTION 3. Composition/information on ingredients.**

#### 3.1. Substances.

Information not relevant.

#### 3.2. Mixtures.

Contains:

Identification. 1-METHOXY-2-PROPANOL

Conc. %. Classification 67/548/EEC. Classific

Classification 1272/2008 (CLP).

CAS. 107-98-2 EC. 203-539-1 50 - 70

R10. R67

Flam. Liq. 3 H226, STOT SE 3 H336

INDEX. 603-064-00-3 Reg. no. 01-2119457435-35

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

 $T+ = Very\ Toxic(T+),\ T = Toxic(T),\ Xn = Harmful(Xn),\ C = Corrosive(C),\ Xi = Irritant(Xi),\ O = Oxidizing(O),\ E = Explosive(E),\ F+ = Extremely Flammable(F+),\ F = Highly\ Flammable(F),\ N = Dangerous\ for\ the\ Environment(N)$ 

## **SECTION 4. First aid measures.**

# 4.1. Description of first aid measures.

EYES: Remove contact lenses, if present Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

# **SECTION 5. Firefighting measures.**

#### 5.1. Extinguishing media.

# SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT



Revision nr. 1

Dated 11/7/2013

Printed on 11/07/2013

Page n. 3/10

**SPMBPI - BPI inks series** 

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture.

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

## 5.3. Advice for firefighters.

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6. Accidental release measures.**

## 6.1. Personal precautions, protective equipment and emergency procedures.

#### FOR LIQUID PRODUCTS:

Block the leakage if there is no hazard.

FOR SOLID PRODUCTS:

If there are no contraindications, spray powder with water to prevent the formation of dust. Avoid breathing vapours/mists/gases.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

#### 6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up.

FOR LIQUID PRODUCTS: Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

FOR SOLID PRODUCTS: Use spark-proof mechanical equipment to collect the leaked product and place it in containers for recovery or disposal. If there are no contraindications, use jets of water to eliminate product residues.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage.**

# 7.1. Precautions for safe handling.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.



SPMBPI - BPI inks series

Revision nr. 1

Dated 11/7/2013

Printed on 11/07/2013

Page n. 4/10

## 7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

## 7.3. Specific end use(s).

Information not available.

# **SECTION 8. Exposure controls/personal protection.**

#### 8.1. Control parameters.

Regulatory References:

United Kingdom EH40/2005 Workplace exposure limits. Containing the list of workplace exposure

limits for use with the Control of Substances Hazardous to Health Regulations (as

amended).

Éire Code of Practice Chemical Agent Regulations 2011.

OEL EU Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive

2000/39/EC.

TLV-ACGIH ACGIH 2012

## 1-METHOXY-2-PROPANOL

#### Threshold Limit Value.

יַד	ype	Country	TWA/8h		STEL/15min		
			mg/m3	ppm	mg/m3	ppm	
W	/EL	UK	375	100	560	150	SKIN
0	EL	IRL	375	100	568	150	
0	EL	EU	375	100	568	150	SKIN
TI	LV-ACGIH		369	100	553	150	

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

## 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration. Personal protection equipment must comply with the rules in force indicated below.

#### HAND PROTECTION

Protect hands with category I (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in latex, PVC or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves` limit depends on the duration of exposure.

#### EYE PROTECTION

Use of protective airtight goggles (ref. standard EN 166) recommended.

## SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.



SPMBPI - BPI inks series

Revision nr. 1

Dated 11/7/2013

Printed on 11/07/2013

Page n. 5/10

## RESPIRATORY PROTECTION

If the threshold value (if available) for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of respiratory tract protection equipment, such as masks like that indicated above, is necessary to reduce worker exposure in the absence of technical measures. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

#### ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9. Physical and chemical properties.**

#### 9.1. Information on basic physical and chemical properties.

Appearance liquid

Colour as showed in color folder Odour alcoholic

Odour threshold. Not available. Not available. Not available. Melting or freezing point. Initial boiling point. > 78 °C. Boiling range. Not available. Flash point. > 23 °C. **Evaporation Rate** Not available. Flammability of solids and gases flammable gas Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Not available. Vapour density

Specific gravity. 0,950 Kg/l
Solubility immiscible with water

Partition coefficient: n-octanol/water
Ignition temperature.

Decomposition temperature.

Not available.
Not available.
Not available.
Viscosity

8-15 cps

Explosive properties

Oxidising properties

Not available.

Not available.

## 9.2. Other information.

VOC (Directive 1999/13/EC): 70,00 % - 665,00 g/litre. VOC (volatile carbon): 37,05 % - 351,98 g/litre.

## **SECTION 10. Stability and reactivity.**

## 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

1-METHOXY-2-PROPANOL: absorbs and disolves in water and in organic solvents, dissolves various plastic materials; it is stable but with air it may slowly form explosive peroxides.



SPMBPI - BPI inks series

Revision nr. 1

Dated 11/7/2013

Printed on 11/07/2013

Page n. 6/10

# 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

## 10.3. Possibility of hazardous reactions.

The vapours may also form explosive mixtures with the air.

1-METHOXY-2-PROPANOL: can react dangerously with strong oxidising agents and strong acids.

#### 10.4. Conditions to avoid.

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

1-METHOXY-2-PROPANOL: avoid exposure to the air.

#### 10.5. Incompatible materials.

1-METHOXY-2-PROPANOL: oxidising agents, strong acids and alkaline metals.

#### 10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

# **SECTION 11. Toxicological information.**

# 11.1. Information on toxicological effects.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

1-METHOXY-2-PROPANOL: the main way of entry is the skin, whereas the respiratory way is less important owing to the low vapour tension of the product. Concentrations above 100 ppm cause eye irritation, nose and oropharynx. At 1000 ppm disturbance in the equilibrium and severe eye irritation is observed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and ocular irritation on direct contact. No chronic effects have been reported in man.

1-METHOXY-2-PROPANOL LD50 (Oral). 5300 mg/kg Rat LD50 (Dermal). 13000 mg/kg Rabbit LC50 (Inhalation). 54,6 mg/l/4h Rat

# **SECTION 12. Ecological information.**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

# 12.1. Toxicity.

Information not available.

# 12.2. Persistence and degradability.



Revision nr. 1

Dated 11/7/2013

Printed on 11/07/2013

1210

Page n. 7/10

# SPMBPI - BPI inks series

Information not available.

#### 12.3. Bioaccumulative potential.

Information not available.

## 12.4. Mobility in soil.

Information not available.

#### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

# **SECTION 13. Disposal considerations.**

#### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information.**

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

UN:

## Road and rail transport:

100
3

ADR/RID Class: 3
Packing Group: III
Label: 3
Nr. Kemler: 30
Limited Quantity. 5 L
Tunnel restriction code. (D/E)

Proper Shipping Name: PRINTING INK or PRINTING INK RELATED MATERIAL

Special Provision: 640E

# Carriage by sea (shipping):



IMO Class: 3 UN: 1210

Packing Group: III

Label: 3

EMS: F-E, S-D

Marine Pollutant. NO



Revision nr. 1

Dated 11/7/2013

Printed on 11/07/2013

Page n. 8/10

SPMBPI - BPI inks series

Proper Shipping Name:

PRINTING INK or PRINTING INK RELATED MATERIAL

Transport by air:

IATA: 3 UN: 1210

Packing Group:

Label: 3

Cargo:

Packaging instructions: 366 Maximum quantity: 220 L

Pass.:

Packaging instructions: 355 Maximum quantity: 60 L

Special Instructions: A3, A72

Proper Shipping Name: PRINTING INK or PRINTING INK RELATED MATERIAL

# **SECTION 15. Regulatory information.**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. 6

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point. 3 - 40

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 689/2008:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.



Revision nr. 1

Dated 11/7/2013

Printed on 11/07/2013

Page n. 9/10

# SPMBPI - BPI inks series

No chemical safety assessment has been processed for the mixture and the substances it contains.

## **SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R10 FLAMMABLE.

R67 VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as Reach Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

## GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
- 8. The Merck Index. 10th Edition
- Handling Chemical Safety
   Niosh Registry of Toxic Effects of Chemical Substances
- 11. INRS Fiche Toxicologique (toxicological sheet)
- 12. Patty Industrial Hygiene and Toxicology
- 13. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition



**SPMBPI - BPI inks series** 

Revision nr. 1

Dated 11/7/2013

Printed on 11/07/2013

Page n. 10/10

## 14. ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.