

Product information | TECHNICAL DATA SHEET

MATT FIXER LACQUER

400 ml, 10.2 Oz , 289 g

GENERAL DESCRIPTION

Clearcoat, non-yellowing, fast drying, matte fixative. Ideal as a fixative and protective coat on objects used indoors.

FEATURES

- Very fast drying.
- Excellent matt finish.
- Not weather or water resistant
- Easy application for protecting different artistic techniques.

APPLICATIONS

Recommended for use in the fine arts for protecting pastel, pencil, watercolor, and charcoal drawings, and when a protective matte coat is required.

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply 1-3 coats of the product depending on the material that needs protection. Do a test prior to doing the final coat. Depending on the thickness of the layer applied, it may slightly whiten the surface's original color.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within ten minutes with the same lacquer.
- Turn the aerosol upside down to clean out the valve after use. If the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

| | |
|---|-------------------------|
| Type de liant: | Additive solution |
| Color: | Colorless |
| Dry to the touch (ASTM D-1640 ISO 1517): | 10' |
| Completely dry (ASTM D-1640 ISO 1517): | 20' |
| Thickness of dry layer (ASTM D-823 ISO 2808): | 15 µ/capa |
| Adherence (ASTM D-3359 ISO 2409): | 4B |
| Theoretical yield (pintado en continuo): | 2 m² |
| Thinner: | Aromatics |
| Product life: | >2 años |
| Recoating: | After 10 minutes |
| Heat resistance of paint: | 100°C |
| Condition for application: | T° min 8°C |
| | T° surface 5°C |
| | Humidity max. 85% R.H.P |

*The adhesion tests were done on PP (EPDM modified). Last revision date: 31/01/2014

CAUTION



APPARENCE



LABEL



EX014S0914 Plastic Primer

CAP SYSTEM



PACKAGING

Nominal capacity 400ml.
Heat resistance of packaging : <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

