mtn de MONTANA COLORS

94 SPECIALTY PRODUCTS

Product information | TECHNICAL DATA SHEET

EXPANDING POLISTYRENE Prepares and primes surfaces to be painted.
400 ml, 11,8 Oz , 334g

GENERAL DESCRIPTION

Grey acrylic primer that brings to expanded polystyrene surfaces a protection that allows post-painted with solvent based paints.

FEATURES

- Very fast drying
- Easy to apply and recoat
- Doesn't content lead
- Perfect adhesion
- Good coverage and filling capability

APPLICATIONS

Indicated, as a primer layer to protect the expanded polystyrene in:

- Modeling - Crafts - Layouts

INSTRUCTIONS FOR USE

- Before using, shake the aerosol vigorously for approximately one minute after the noise of the mixer starts. Paint with the container upright. Apply quick and fine layers at a distance of about 20cm past.
- To obtain a perfect protection of the expanded polystyrene, it is important to cover accurately the whole surface, preventing unpainted pores or spaces. We recommend applying a minimum of 5 thin layers, leaving 5-10 minute drying intervals between each layer.
- Once dry for 30 min apply any type of paint, hence avoiding any damage to the polystyrene.
- Don't spray on plugged-in equipment and use it only in well ventilated areas.
- Ask for MSDS.

PHYSICAL PROPERTIES

Binder:	Acrylic
Color:	Grey R.7001
Dry to touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517):	30'
Dryfilm thickness (ASTM D-823 ISO 2808):	10-15 µ/layer (2pasadas)
Adherence (ASTM D-3359 ISO 2409):	n/a
Theorical yield (pintado en continuo):	2 m²
Thinner:	Alcohol
Product life:	>2 years
Recoating:	After 10'
Heat resistance:	n/a
Condition for application:	Tº min 8ºC
	Tº surface 5ºC-50ºC
	Humidity max. 85% R.H.P

*The adhesion tests were done on PP (EPDM modified). Last revi ew's date: 31/01/2014.

CAUTION

Erittäin syttyvä
Εύφλεκτο
Extremely flammable
Extremadamente inflamable
Extremadament inflamable
Yderst brandfarlig
Extrêmement inflammable

可燃性激烈
Meget brannfarlig
Wysoce łatwopalny
Extremt lättantändlig
легкосгораемый
Zeer licht ontvlambaar
Extremadamente inflamável
Estremamente infiammabile

Nocivo
Nociu
Nocif
Hamful
Επιβλαβές
Gesundheitsschadlich
Terveydelle haitallinen

有害
Nocivo
Giftig
Nocivo
Drazniacy
Schadelijk
Hälsoskadlig
вредный для здоровья

FLAMMABLE GAS 2

KEEP PLANET CLEAN

APPARENCE

LID
Protects the valve and the nozzle.

DONUT
Indicates the paint color.

LABEL

REF. N# Nombre del color
Color name

COD. BARRAS/BAR CODE

Nº EX
Lote fabricación
Envasado / Caducidad

Nivel opacidad — Resistencia exterior

EX014S1043 Poliestireno expandido

CAP SISTEM

Pocket Cap
Fino - Thin

PACKAGING

Nominal capacity 400ml.
Heat resistanve of packaging : <50ºC
Propellant: GLP – HC C_3-C_4

Box (6 units)
205 X 140 X 200 mm.

mtn

Montana Colors, S.L. P.I. Clot del Tufau - 08295 Sant Vicenç de Castellet BARCELONA
T.: +34 938 332 787 F: +34 93 833 08 75 - montana@montanacolors.com - www.montanacolors.com

TÜVRheinland CERTIFIED Management System ISO 9001:2008 ISO 14001:2004 www.tuv.com ID 9105036640

Empresa certificada según norma de calidad
ISO 9001:2000
ISO 14001:2004
Made in Europe.