

## Product information | TECHNICAL DATA SHEET

**FLUORESCENTS.** Fluorescent spray paint.  
400 ml, 10.6 Oz, 300 g.

### GENERAL DESCRIPTION

Fluorescent spray paint composed of acrylic solvent-based resins and thermoplastic copolymers, combined with fluorescent pigments (hypnotic) to produce very bright finishes. Its formula consists of opaque base additives that provide greater coverage and make it possible to work directly on dark backgrounds.

### FEATURES

- Fast drying.
- Very bright colors.
- Easy to apply.
- Matte finish.
- Does not contain lead nor other heavy metals.
- Can be applied to many materials.
- Can be applied to damp surfaces.
- Very low UV resistance to sun.
- Can be varnished with an acrylic varnish.

### INSTRUCTIONS FOR USE







- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush. Apply an anchor layer on plastics and polyesters.
- To obtain a better, brighter finish, apply a layer of matte white prior to painting.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within ten minutes with the same paint.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

### PHYSICAL PROPERTIES

Binder:	Acrylic thermoplastic
Color:	See chart
Shine:	<10%
Dry to touch (ASTM D-1640 ISO 1517):	5 min
Total drying (ASTM D-1640 ISO 1517):	10 min
Dryfilm thickness (ASTM D-823 ISO 2808):	15 µ/layer
Theoretical yield ( pintado en continuo):	2 m <sup>2</sup>
Thinner:	Butyl acetate
Product life:	>5 years
Heat resistance:	150 °C
Condition for application:	T° min 8°C
	T° surface 5°C-50°C
	Humidity max. 85% R.H.P

Last reviw's date: 15/11/2014

### COLORS

		
EX0140600M Yellow	EX0140601M Orange	EX0140602M Red
		
EX0140603M Fucsia	EX0140605M Blue	EX0140604M Green

### ATENCIÓN



### APPLICATIONS

Due to the characteristics of this product, we recommend its use for the following applications:

- DIY
- Industry
- Safety
- Graffiti
- Topographical signs.
- Forestry works
- Construction
- Geological studies
- Sports racing
- Mining
- Sign painting
- Shows

### APPARENCE



### LABEL



### CAP SYSTEM



### PACKAGING

Nominal capacity 400 ml.  
Heat resistance of packaging: <50°C  
Propellant: DME

**Box (6 units)**  
205 X 140 X 200 mm.

