

Product information | TECHNICAL DATA SHEET

EPS PRIMER (STYROFOAM). Prepares and primes surfaces to be painted.
400 ml, 11.1 Oz, 317g.

GENERAL DESCRIPTION

Grey acrylic primer that brings to expanded polystyrene surfaces a protection that allows post-painted with solvent based paints.

FEATURES

- Very fast drying.
- Easy to apply and recoat.
- Doesn't content lead.
- Perfect adhesion.
- Good coverage and filling capability.

APPLICATIONS

Indicated, as a primer layer to protect the expanded polystyrene in:

- Modeling
- Crafts
- Layouts
- Architectural Studies

INSTRUCTIONS FOR USE

- Before using, shake the aerosol vigorously for approximately one minute after the noise of the mixer starts. Paint with the container upright. Apply quick and fine layers at a distance of about 20cm past.
- To obtain a perfect protection of the expanded polystyrene, it is important to cover accurately the whole surface, preventing unpainted pores or spaces. We recommend applying a minimum of 5 thin layers, leaving 5-10 minute drying intervals between each layer.
- Once dry for 30 min apply any type of paint, hence avoiding any damage to the polystyrene.
- Don't spray on plugged-in equipment and use it only in well ventilated areas.
- Ask for MSDS.

PHYSICAL PROPERTIES

Binder:	Acrylic
Color:	Grey R.7001
Dry to touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517):	30'
Dryfilm thickness (ASTM D-823 ISO 2808):	10-15 µ/layer (2pasadas)
Adherence (ASTM D-3359 ISO 2409):	n/a
Theoretical yield (pintado en continuo):	2 m ²
Thinner:	Alcohol
Product life:	>5 years
Recoating:	After 10'
Heat resistance:	n/a
Condition for application:	T° min 8°C
	T° surface 5°C-50°C
	Humidity max. 85% R.H.P

*The adhesion tests were done on PP (EPDM modified). Last rev ew's date: 2/01/2017.

CAUTION



APPARENCE



LABEL



EX014PR0914 EPS Primer

CAP SYSTEM



PACKAGING

Nominal capacity: 400 ml.
Heat resistance of packaging: <50°C
Propellant: GLP – HC C₃-C₄

Box (6 units)
205 X 140 X 200 mm.

