

Información de producto | FICHA TÉCNICA

WASH PRIMER

400 ml, 10.9 Oz, 309 g. NET WT.

GENERAL DESCRIPTION

Phosphate Primer (Wash Primer) with excellent adhesion on galvanized and zinc electroplated steel, aluminum, and all types of polished metals. Also works very well as a primer layer on some plastics.

FEATURES

- Fast drying.
- Easy to apply and repaint.
- Good adherence.
- Does not contain lead.

APPLICATIONS

Recommended to be utilized as a primer layer on galvanized metal surfaces such as:

- Garage doors or metal shutters.
- Copper pipes.
- Aluminum profiling.

Also usable as a primer on polyamide 6 plastic surfaces, carbon fiber, epoxy, polyester, acrylate, PVC, PC, and ABS. The product's characteristics make it very adequate on pre-sanded surfaces painted with polyester-type paints (aluminum profiling) or on 2K epoxy.

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush. Due to the multitude of substrates and methods for application, it is recommended to do a test on the material prior to application.
- Apply in thin, even layers to obtain the best results. Second coat may be applied after 20 mins. May be repainted with other products after 2 hours. Check compatibility by testing.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

Type of liant:	Resin mixture
Color:	Grey
Dry to the touch (ASTM D-1640 ISO 1517):	20'
Completely dry (ASTM D-1640 ISO 1517):	2 h
Thickness of dry layer (ASTM D-823 ISO 2808):	7-15 micras/layer
Adherence (ASTM D-3359 ISO 2409):	B
Theoretical yield (continuous painting):	2 m ² for 400 ml
Thinner:	Solvent mixture
Product life:	(Well Stored) 5 Years
Condition for application:	Minimum room temperature 8°C Surface temperature 5°C a 50°C Max humidity, 85% R.H.P

* Adhesion tests have been carried out on galvanized steel plates. Fecha última revisión: 14/01/2016.

CAUTION



APPEARANCE



LABEL



EX014PR0133 Wash Primer

CAP SYSTEM



PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

