

## Product information | TECHNICAL DATA SHEET

### SEAL-COATING.

400 ml, 10,68 Oz, 303 g.

#### GENERAL DESCRIPTION

Rubber-based paint, ideal for sealing leaks or small cracks in roofs, metal and plastic pipes and PVC pipes in general. It creates a waterproof, flexible coat that protects and waterproofs all types of surfaces.

#### CHARACTERISTICS

- Fast-drying.
- Excellent flexibility.
- Easy to apply and repaint.
- Excellent adhesion on porous surfaces.
- High sealing and waterproofing potential.
- High opacity.

#### INSTRUCTIONS FOR USE

- Shake the spray can well before use for about one minute after hearing the sound of the mixer ball.
- Prepare and properly clean the area to be sealed/protected before applying the product. Remove dust; sand and clean polished metals and remove old paint. Ensure for a good adhesion depending on the material of the surface to be repaired.
- Apply the product on the area you wish to repair and around it at a distance of 20-30 cm. Apply two coats for best results. Depending on the size of the crack, more coats may be necessary.
- Repaint after 20-30' minutes with the same paint.
- Invert the spray can to purge the valve after use. If the cap becomes clogged replace it with a new one.
- Do not apply to plugged-in electronic equipment and use in well-ventilated areas.
- Request safety data sheets.

#### GENERAL DESCRIPTION

Binder type:	Special resin
Color:	Black, teak red y white
Dry to the touch (ASTM D-1640 ISO 1517):	30-45'
Total dry time (ASTM D-1640 ISO 1517):	24 h (2 coats)
Thickness of dry coat (ASTM D-823 ISO 2808):	<60 µ/coat
Theoretical performance (continuous painting):	1-1,25 m <sup>2</sup> ; 2 coats 0,6-0,75 m <sup>2</sup>
Thinner:	Water /Alcohol
Shelf life:	< 5 años (Correctly stored)
Condiciones de aplicacion:	Atmospheric temp. 10-35°C
	Surface temp 5°-50 C
	Max. Humidity: 85% R.H.P

\* Times may vary depending on thickness of coat.

#### LABEL



#### CAP SYSTEM



#### APPLICATION

Due to the characteristics of this product we recommend using it for sealing, protecting and/or waterproofing:

- Terraces, balconies, roofs.
- Metal or plastic pipes (drains, PVC pipes).
- Waterproofing of damp areas.
- Wooden objects inside and outside (tables, chairs, benches).

#### APPARENCE



#### PACKAGING

Capacity 400 ml.  
Packaging heat resistance: <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm



#### CAUTION

